

Boat Manufactured By:



2805 Decio Drive • Elkhart, IN 46514
(574) 264-6336
www.benningtonmarine.com

BENNINGTON 22 SCCTTX

Length	23' 3"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,733 lbs
Maximum HP	200 hp
Fuel Capacity	51 gal
Weight as Tested	3,980 lbs

F150XB

Horsepower	150 hp
Induction	EFI/DOHC
Displacement	2.7L
Weight (Estimated)	489 lbs
Gear Ratio	2.00:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1
------------------------	----

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	14-1/2 x 14
Yamaha Part #	68F-45930-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	66° F / 72° F
Elevation (in feet above sea level)	850'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 40 gallons of fuel, 1 battery, safety and test equipment.

YPB#: PB_BNT_22 SCCTTX_F150XB_8-17-20_PNT



Engine: Yamaha F150XB

Boat: Bennington 22 SCCTTX

Configuration: Single

Test Date: 16-Aug-2020



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.8	0.8	4.75
1500	5.2	1.2	4.48
2000	7.1	1.8	3.92
2500	8.9	2.7	3.30
3000	13.6	3.6	3.76
3500	18.2	5.1	3.57
4000	21.9	6.5	3.37
4500	25.5	8.5	2.99
5000	29.2	10.7	2.73
5500	32.7	13.8	2.37
5900	34.8	15.9	2.19
0-20 MPH: 5.18 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.