

Boat Manufactured By:



P.O. Box 26 • Amory, MS 38821

(662) 256-5636

www.nauticstarboats.com

NAUTIC STAR® 244 XTS

Length	24' 6"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,500 lbs
Maximum HP	300 hp
Fuel Capacity	80 gal
Weight as Tested	4,080 lbs

F300XCA

Horsepower	300 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	562 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2 on Hydraulic Jack Plate
Ventilation Plate Height	4 1/4" Above Boat Bottom (Plate Set at 1.5)

PROPELLER(S)

Series	Pro Series™
Diameter x Pitch	14 1/2 x 21
Yamaha Part #	6J9-45976-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	85° F / 78° F
Elevation (in feet above sea level)	440'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 1/2 tank of fuel, 1 battery, Power Pole, optional T-top, safety and test gear.

YPB#: PB_NST_244XTS_F300XCA_2014-07-14_BAY



Engine: Yamaha F300XCA

Boat: Nautic Star® 244 XTS

Configuration: Single

Test Date: 14-Jul-2014



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.8	1.3	3.69
1500	6.7	2.2	3.05
2000	8.4	3.5	2.4
2500	10.2	5.1	2
3000	20.6	6.2	3.32
3500	29.5	7.8	3.78
4000	36.3	10.5	3.46
4500	42	13.8	3.04
5000	47.4	17.2	2.76
5500	53.4	20.6	2.59
6000	59.1	26	2.27
Time to Plane: 3.52			
0-30 MPH: 5.74			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.