

Boat Manufactured By:



One Skeeter Road • Kilgore, TX
(903) 984-0541

www.skeeterboats.com

SKEETER SX2350

Length	22' 9"
Beam	8' 5"
Dry Weight (Boat Mfr. Pub)	3,075 lbs
Maximum HP	250 hp
Fuel Capacity	55 gal
Weight as Tested	4,742 lbs

VF250XB

Horsepower	250 hp
Induction	EFI/DOHC
Displacement	4.2L
Weight (Estimated)	567 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15 x 20
Yamaha Part #	6CE-45932-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	80° F / 85° F
Elevation (in feet above sea level)	338'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 50 gallons of fuel, 4 batteries, 36V Trolling motor, 12" fixed setback, safety and test equipment.

YPB#: PB_SKT_SX2350_VF250XB_09/22/21_BAY



Engine: Yamaha VF250XB

Boat: Skeeter SX2350

Configuration: Single

Test Date: 21-Sep-2021



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.7	1.3	3.61
1500	7.0	2.3	3.01
2000	8.7	3.7	2.35
2500	12.9	5.5	2.32
3000	26.3	6.5	4.04
3500	33.4	9.4	3.56
4000	38.7	12.1	3.20
4500	42.6	15.7	2.71
5000	47.7	19.3	2.47
5500	52.7	22.2	2.38
5900	55.1	23.6	2.34
0-20 MPH: 4.86 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag, and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.