

Boat Manufactured By:



One Skeeter Road • Kilgore, TX

(903) 984-0541

www.skeeterboats.com

SKEETER® ZX 24 V®

Length	24' 1"
Beam	8' 5"
Dry Weight (Boat Mfr. Pub)	2,840 lbs
Maximum HP	300 hp
Fuel Capacity	80 gal
Weight as Tested	4,162 lbs

F250XCA

Horsepower	250 hp
Displacement	4.2 L
Weight (Estimated)	558 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™-SDS™
Diameter x Pitch	15.25 x 19
Yamaha Part #	6CE-45970-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	1
Air / Water Temperature (Fahrenheit)	51° F / 57° F
Elevation (in feet above sea level)	640'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 70 gallons of fuel, 1 battery, bow-mounted trolling motor, battery charger, safety and test equipment. Fuel consumption data gathered with Yamaha Command Link® fuel management system. Zero-to-30 speed data gathered with radar gun. Other speed data gathered with GPS receiver. This propeller was tested for information purposes only. Please consult dealer for actual prop selection based on intended use of your particular boat.

YPB#: PB_SKT_ZX24V_F250XCA_2010-12-14_BAY



Engine: Yamaha F250XCA

Boat: Skeeter® ZX 24 V®

Configuration: Single

Test Date: 14-Dec-2010



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.5	1.2	4.58
1500	7.6	2.3	3.3
2000	9.6	3.5	2.74
2500	17	4.8	3.54
3000	27	6	4.5
3500	33.2	7.7	4.31
4000	37.8	10.4	3.64
4500	42.4	13.6	3.12
5000	47.2	17	2.78
5500	51.7	20.8	2.49
5900	55.4	24.2	2.29
Seconds to Plane: 3.31			
Seconds 0-30 MPH: 5.09			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.