

PERFORMANCE BULLETIN

Engine: Yamaha VF250XA V

MAX SHO®

Boat: Solera 205


Configuration: *Single* **Test Date:** 7-Feb-2018



PERFORMANCE DATA

RPM	МРН	GPH	MPG
1000	5.4	1.3	4.12
1500	7.1	2.4	2.94
2000	8.6	3.7	2.31
2500	19.1	5.0	3.81
3000	28.4	6.3	4.50
3500	33.7	8.5	3.98
4000	38.9	11.3	3.45
4500	43.9	15.3	2.87
5000	48.5	18.2	2.66
5500	53.5	23.0	2.32
6000	58.1	24.5	2.37

Time to Plane: 3.13 seconds 0-30 MPH: 4.51 seconds



NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.



SOLERA 205

Length	20' 5"
Beam	8' 4"
Dry Weight (Boat Mfr. Pub)	2,725 lbs
Maximum HP	250 hp
Fuel Capacity	41 gal
Weight as Tested	4,227 lbs

VF250XA V MAX SHO®

Horsepower	250 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	555 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position #3 on 8" Manual Jack Plate

PROPELLER(S)

SeriesSaltwater Series II™Diameter x Pitch15-1/4 x 19Yamaha Part #6CE-45970-20-00Propeller MaterialPolished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	38° F / 60° F
Elevation (in feet above sea level)	338'
Wind Velocity	0-5 MPH

COMMENTS

Tested with 2 people, 39 gallons of fuel, 36-volt bow mounted trolling motor, 4 batteries, onboard battery charger, safety and test equipment.

YPB#: PB_SKT_Solera205_VF250XA_020718_WLY

Boat Manufactured By:

Skeeter

One Skeeter Road • Kilgore, TX

(903) 984-0541

www.skeeterboats.com (http://www.skeeterboats.com)

