

Boat Manufactured By:



One Skeeter Road • Kilgore, TX
(903) 984-0541

www.skeeterboats.com

SKEETER® ZX 250

Length	20' 11"
Beam	7' 11"
Dry Weight (Boat Mfr. Pub)	2,085 lbs
Maximum HP	250 hp
Fuel Capacity	44 gal
Weight as Tested	3,460 lbs

VF250LA

Horsepower	250 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	505 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
Jack Plate	Manual

PROPELLER(S)

Series	VMAX® Ventless Series
Diameter x Pitch	15 1/8 x 25
Yamaha Part #	6CB-45972-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	73° F / 88° F
Elevation (in feet above sea level)	230'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 22 gallons of fuel, 4 batteries, bow-mount trolling motor, 4-bank onboard battery charger, Power Pole, 12" manual jack plate, safety and test gear.

YPB#: PB_SKT_ZX250_VF250LA_2014-08-24_BSS



Engine: Yamaha VF250LA

Boat: Skeeter® ZX 250

Configuration: Single

Test Date: 24-Aug-2014



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.6	1.5	3.73
1500	7.2	2.8	2.57
2000	8.1	4.1	1.98
2500	12.3	5.9	2.09
3000	32.1	6.9	4.65
3500	39.1	9.3	4.2
4000	44.8	12.2	3.67
4500	53.3	15.2	3.51
5000	60.1	17.3	3.47
5500	66.4	20.1	3.3
6050	72.3	23.1	3.13
0-30 MPH: 5.59			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag, and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.