

Boat Manufactured By:


 2805 Decio Drive • Elkhart, IN 46514
 (574) 264-6336

www.benningtonmarine.com
BENNINGTON® 2250 GSR

Length	24' 1"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,505 lbs
Maximum HP	200 hp
Fuel Capacity	35 gal
Pontoons (#/Diameter)	2 / Elliptical
Weight as Tested	3,644 lbs

VF200LA

Horsepower	200 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	505 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	14 1/4" x 17
Yamaha Part #	68F-45972-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	38° F / 44° F
Elevation (in feet above sea level)	785'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 20 gallons of fuel, 1 battery, safety and test gear. Tested with foils and lifting strakes.

YPB#: PB_BNT_2250GSR_VF200LA_2013-04-24_PNT

Engine: Yamaha VF200LA

Boat: Bennington® 2250 GSR

Configuration: Single

Test Date: 24-Apr-2013

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.6	1.3	3.54
1500	5.9	2	2.95
2000	7.1	2.7	2.63
2500	8.6	3.7	2.32
3000	12	4.9	2.45
3500	16.2	6.8	2.38
4000	22.1	8.7	2.54
4500	31.2	11.8	2.64
5000	38	14.1	2.7
5500	42.6	17.5	2.43
6050	48.2	19.2	2.51
Seconds 0-30 MPH: 6.39			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.