

Boat Manufactured By:



300 West Chicago Street • Syracuse, IN 46567

(574) 457-5731

www.larsonfx.com

LARSON® FX 2020 DC

Length	20' 2"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,240 lbs
Maximum HP	250 hp
Fuel Capacity	53 gal
Weight as Tested	4,124 lbs

F250XCA

Horsepower	250 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	562 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™-SD5™
Diameter x Pitch	15 1/4 x 18
Yamaha Part #	6CE-45934-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	72° F / 73° F
Elevation (in feet above sea level)	940'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 26 gallons of fuel, 5 batteries, bow-mounted trolling motor, Minn Kota Engine Mount Motor, 2 Minn Kota Shallow Water Anchors, safety and test gear.

YPB#: PB_LAR_FX2020DC_F250XCA_2013-09-06_WLY



Engine: Yamaha F250XCA

Boat: Larson® FX 2020 DC

Configuration: Single

Test Date: 6-Sep-2013



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.2	1.2	4.33
1500	7.2	2.1	3.43
2000	8.6	3.6	2.39
2500	13	5.2	2.5
3000	24.4	6.3	3.87
3500	30.9	8.5	3.64
4000	35.7	11.3	3.16
4500	40.4	15	2.69
5000	45.2	17.4	2.6
5500	49.7	20.4	2.44
5900	52.4	23.4	2.24
0-30 MPH: 6.5			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.